

RapidSAT LBT 9522BRS



- **Global Coverage**
- Rapidly Deployable
- Grab and Go
- All-In-One Kit
- First Responder

RapidSAT LBT provides a high quality portable calling solution, using superior echo cancelling and full duplex technologies to provide superior voice quality. The RapidSAT LBT enables handsfree or privacy calls. This is contained within a lightweight and durable carry bag ready for use anytime, anywhere.

The purpose built RapidSAT LBT provides integrated antenna, data and power connections that makes it possible to keep all antenna cables and power permanently connected to the handset and allows for the bag to be ready at all times.

The Intelligent handset supplied with RapidSAT LBT supports both handsfree and privacy modes of operation automatically switching between either mode with the handset in or out of the cradle.

The flexibility of the RapidSAT LBT enables the unit to be easily transported between various vehicles, boats, machinery or aircraft and simply connects to the vehicle's DC power source for in vehicle use or alternatively the optional battery back-up for away from vehicle use.



Emergency Services/ Disaster Recovery



Temporary Vehicle / Vessel Installations



Remote Tour, Camping and Exploration Groups



Back-up Communications



KEY FEATURES

- Small, tough and lightweight carry bag
- Integrates all required cables & antenna
- ▶ Intelligent Handset SMS capable
- In-built Speaker/Mic
- Full duplex handsfree operation
- Magnetic Mount Antenna, 5m cable
- Power ON/OFF
- Carry handle or shoulder strap

- Additional storage pockets
- ▶ 11-32V DC input
- Supports Voice & Data services
- Loud ring indications
- Echo cancellation
- Optional Battery Pack
- RoHS compliant









oice

Privacy Handset

Handsfree



^{*}RST055 UPS Battery Pack can be ordered separately.

TECHNICAL SPECIFICATIONS

| POWER SPECIFICATIONS | | |
|--------------------------|-------------|-----------|
| Power Input Voltage | 11 - 32 V I | DC @ 4-1A |
| Power Consumption (AMPS) | 12 V DC | 24 V DC |
| Stand by - incl handset | 0.48 | 0.25 |
| Transmit - incl handset | 0.68 | 0.35 |
| Stand by - incl handset | 0.48 | 0 |

N.B. Assumes battery charged

| PHYSICAL SPECIFICATIONS | |
|--------------------------|---|
| Bag Dimensions | 380mmL x 250mmW x 150mmD (15' x 9.8' x 5.9') |
| Antenna Cable Length | 5m (16.4') |
| Power Input Cable Length | 1m (3.3') |
| Weight* | 3.7kg / 8.15lbs |

* Does not include weight with a UPS battery pack

ENVIRONMENT SPECIFICATIONS

| Temperature | Degrees °C | Degrees °F | |
|-----------------|------------------------|-------------|--|
| Operating Range | -30 to +70 | -22 to +158 | |
| UPS Battery | -20 to +60 | -4 to +140 | |
| Humidity | <85% RH non condensing | | |

| CONNECTORS / INTERFACES | DNNECTORS / INTERFACES | | |
|-------------------------|---------------------------|--|--|
| Iridium Antenna | Fixed Cable to TNC-Female | | |
| Power Input | 4W Molex Connector | | |
| Data Port | USB | | |
| Speaker | 3W | | |

CERTIFICATIONS

Iridium - CE, RoHS

Electrical Safety - IEC/EN/AS/NZ60950-1

EMC Compliance - IEC/EN60945 (9 & 10)

KIT CONTENTS

Carry Bag with Intelligent Handset, Speaker & Microphone

Magnetic Mount Antenna with 5m of cable

DC Cigarette plug adaptor for power

ACCESSORIES

RST055 - Beam UPS Battery Back-up

RST750 - Beam AC Plug Pack

Optional RST055 UPS Battery Pack

| Standby Time | Up to 17 hours |
|--------------|----------------|
| Talk Time | Up to 12 hours |

BAG DIMENSIONS





APPROVED BEAM RESELLER

www.beamcommunications.com

+61 3 8588 4500



+61 3 9560 9055



info@beamcommunications.com

AFRICA

ASIA

AUSTRALIA

EUROPE

MIDDLE EAST

NORTH AMERICA

SOUTH AMERICA